



SmartStart Pro

Our most economical payment terminal is a great choice for C-Stores and In-Bay Automatic Washes.

It's the smart way to get started! As one of the most affordable payment terminals on the market, the new SmartStart Pro cost-effectively enables secure car wash transactions. Powered by our WashConnect management software, the 10.4" touchscreen and multiple cashless payment options help speed your customers through the purchase. Customizable decals, graphics and videos reinforce your brand and offer the ability to cross-promote other products. All this while you easily access real-time financial results from your PC, tablet or mobile. Get started today!

SmartStart Pro

SmartStart Pro Features & Benefits

- 10.4" full-sunlight-readable touchscreen display, combined with an intuitive user interface, supports a quick and easy transaction as well as a positive customer experience
- Provides your customers with the convenience of multiple contactless payment options: EMV, Tap N Pay, Mobile Pay, gift card, fleet card, wash book, wash code, RFID/LPR, ePOS, and mobile app
- Customizable decals, on-screen graphics, videos, and animations complement your brand, help effectively market your car wash program, and enable cross marketing of products in other key categories: Food Service, Beverages, etc.
- Efficiently manage your car wash program with real-time financial information that is easily accessible from your PC, tablet, or smartphone

- Ensure the health of your car wash network by accessing uptime statistics and detailed event logs, or receive e-mail alerts for your payment terminals as well as select car wash equipment
- Simplify your PCI compliance requirements and protect your customer's credit card data with the most secure payment process possible, validated point-to-point encryption
- Supports multiple languages



Requirements & Specifications

- Width: 53.34 cm
- Height: 40.64 cm (SmartStart Pro terminal)
99.695 cm (SmartStart Pro optional base)
140.335 cm (Smartstart Pro terminal and optional base)
- Depth: 45.72 cm (with heat exchanger)
- Weight: 32.2051 kg (SmartStart Pro terminal)
15.4221 kg (SmartStart Pro optional base)
47.6272 kg (Smartstart Pro terminal and optional base)
- Operating Temperature Range:
 - -29° C to 60° C
- Frequency: 50/60 Hz
- Supply Voltage:
 - 120 VAC
 - 240 VAC
- Max. Current:
 - 10 Amps @ 120 VAC
 - 5 Amps @ 240 VAC
- IPX RATING: NEMA 4X



psdcodax.com